

# Truck Mounted Patcher



**Apply Tack Coat**



**Inject Emulsion  
Aggregate Mixture**



**Cover With Dry  
Aggregate**



The same over the top quality and features of our trailer mount patchers. With the added benefit of easier maneuverability of a truck mount. It has a large 6 yard hopper for aggregate. You can have the truck mount as a the standard T7500 or the Vortex with its larger high performance 60 cfm air compressor.

## Economical

- Material cost is about 1/2 **the cost** of cold mix
- Repairs last for years
- Store materials on-site for **increased efficiency**
- **No other equipment necessary**= aggregate is supplied by your dump truck. The Vortex does the rest!
- Produce **20 tons (or more)** of road repair patch **daily**

## Will Repair

- Potholes
- Alligator Cracks
- Shoulder Failures
- Utility Cuts
- Cracks (using crack seal attachment)
- Many other common road repairs

# Total Patcher Features:

## Emulsion Tank

- **Size** - 250 U.S. gal; 12-inch filler cap for added safety and convenience, 2" drain valve
- **Working Pressure** - 200 psi @ 500° F pressure relief set from 100-110 psi
- **Insulation** - R-15 rating with a fire retardant fiber reinforced plastic cover
- **Heat** - Two 1500w radiant heater blankets (120v) with thermostatic control

## Emulsion Line Clean Out Tank

15 U.S. gal pressure vessel rated at 200 psi @ 450° F pressure relief set at 175 psi

## Engine Fuel Tank

18.5 U.S. gal steel with quantity gauge

## Compressor

**T7500**=Auxiliary driven 15 cfm continuous duty; governor set @ 125 psi (Emulsion tank regulated @ 90 psi)

**Vortex**= Serpentine belt driven 60 cfm @150 psi rotary compressor Includes 25ft x ¾ retractable air hose reel

## Blower

450 cfm with 7 psi (14 psi potential) @ 1500 rpm, approx 42 BHP. Mounted directly off engine flywheel (requires no belts or pulleys). Protective air pop-off valve set at 10 psi. Normal operating temp under 230° F (max 275° F).

## Air Conveyor Aggregate Feed

Aggregate is injected into the air conveyor system via a low pressure suction created by a venturi (under the hopper box). Slide gate opens and closes by a 4" stroke air ram controlled through a 12v air solenoid valve activated by a remote switch located at operator control handle. Aggregate 1/4" - 1/2" size is normally used. Machine will run up to 1" aggregate, and will allow a 2 1/2" stone to pass through without clogging. Air solenoid valve has manual override for easy servicing.

## Air Filters

- **Engine** - Paper element with vactuator valve in filter housing
- **Compressor** - Paper element with vactuator valve in filter housing
- **Blower** - Paper element with 300 sq inches in filtration surface with foam pre-cleaner

## Mobile Heating System

Engine coolant is routed through a high efficiency heat exchanger filled with heat exchange oil. The heated oil circulates via a 12v circulation pump throughout the emulsion distribution system, including the emulsion storage tank, hoses, and spray nozzle. Average system temp is 140° F. The total patcher can work effectively down to an ambient temp of 0° F (using proper emulsion for those temperatures).

## Vented Nozzle/Spray Tip

**Nozzle** - Lightweight steel tube 3 1/2" x 13" automatically pressure compensates to prevent blowing material out of target area. Promotes clean operation and precise control.

**Spray tip** - Singular heated block with a precession laser cut 1" x .0625" inch slot for dispensing emulsion for 100% aggregate coating.

## Aggregate Hose

Aggregate travels the length of the machine via a 3 1/2" ID schedule 40 pipe, then travels through 3 1/2" ID 192" long rubber neoprene lined hose (wire reinforced to prevent kinks).

## Emulsion Supply/Diesel Clean-Up Line

A 20' long x 1/2" ID hose rated at 2300 psi carries the emulsion to the spray nozzle. Emulsion lines are encased in an insulated line packet to allow for cold weather operation. This line also serves as the clean-up line when patching operations are completed. Clean up takes about 1 quart of liquid.

## Swinging Hose Carrier

**Easy Operation** - Free travel boom system supports the weight of the aggregate hoses. System allows an 18" working travel radius. All operator controls for throttle and aggregate flow are at the handle.

## Frame

- **Frame** - 10 channel x 186"
- **Hopper** - 6 yard
- **Hopper vibe** - 12 Volt
- **Lights** - Brake & tail, side marker, multi-directional/multi-pattern high intensity LED light stick, rear mounted strobe
- **Dimensions** - 96" wide x 81" high x 220" long w/o Truck
- **Weight** - 8970 lbs w/o Truck



Specifications subject to change without notice

## Total Patcher

4614 East 1000 North-Pittsboro, Indiana 46167

Toll Free 866-892-4737-Ph: 317-892-4737- Fax: 317-892-5196

Info@totalpatcher.com - www.totalpatcher.com